



# MANDRELS for KART ENGINES

## type CY44 and CY56

Diameter mm 37,0-55,6 (1.45-2.18)

### Mandrels type CY44 and CY56 with SHORT stones (68 e 80 mm – 2.67" and 3.14")



These lifetime mandrels are specifically designed to work cylinders with radial holes very large as kart cylinders. Stone support and guide-shoe are of proper length to produce straight, round and accurate holes.

The best technical situation is to have a mandrel for each diameter to work. To find the mandrel that you need, be sure that the bore diameter of the cylinder to work is included between the size range of the hone. The diameter for the mainly diffuse capacity are:

- Ø 42 mm (1.653") for 60cc
- Ø 50 mm (1.968") for 100cc
- Ø 54 mm (2.125") for 125cc



SIZE DIAMETER		HONE MANDREL	STONE LENGHT		DIAM. REF.		REF. CAPACITY
mm	inches		mm	in	mm	in	
37,00 – 40,60	1.45 – 1.59	<b>CY44 – 370CR</b>	68	2.67	40	1.57	50cc
41,00 – 44,45	1.61 – 1.75	<b>CY44 – 410CR</b>			42	1.65	60cc
44,20 – 47,60	1.74 – 1.87	<b>CY56 – 440CM</b>	80	3.14	47	1.85	85cc
47,40 – 50,80	1.86 – 2.00	<b>CY56 – 470CM</b>			50	1.96	100cc
50,60 – 54,00	1.99 – 2.12	<b>CY56 – 500CM</b>			52	2.04	100cc
53,80 – 57,20	2.11 – 2.25	<b>CY56 – 530CM</b>			54	2.12	125cc

### Photo Gallery:



## ABRASIVES and DIAMOND STONES

### > Engines with cast iron cylinders of 60cc, 100cc and 125cc

All our hones for kart, use Sunnen abrasive supports that are proposed as ABRASIVE KITS. So, the **ABRASIVE KITS** included stone supports with **the same specifications used in production and on race by some ENGINE BUILDERS.**

The kits are of two types with final suffix "F" or "L" and the mean:

- final suffix "F": means **Finishing** that is a silicon carbide abrasive for finishing with grit 400
- final suffix "L" means **Lapping**, that is an *special mixture abrasive for lapping* with grit 800

So, the abrasive kit composition is the following:

1x abrasive support for Medium Finishing  
1x abrasive support for Finishing or Lapping



Abrasive Kit for CY44. Stone Length = 68 mm (2.67)



Abrasive Kit for CY56. Stone Length = 80 mm (3.14)

### > Engines with Nickel-plated cylinders (*nikasil*®):

Because of the remarkable hardness obtained with nickel treatment, the working with above mentioned abrasives is not possible, so it is necessary to use the **Diamond Stones**. The DIAMOND Stones supplied by us are built with **Resin Bond Diamond Strip** and are available usually in two specifics: **D267** (roughness) **D330** (finishing). Also the **DIAMOND STONE for NICKEL-PLATED cylinders** are those usually used by some **ENGINE BUILDERS**. The Diamond Stone is provided individually or included in a kit composed by two supports:



Diamond Kit for CY56, Length = 80 mm (3.14)

1x Stone support for Roughness (silicon carbide abrasive)  
1x DIAMOND STONE for finishing (**D330**) or roughness (**D267**)  
**Available diamond stone with different grit size.**

## ACCESSORIES

### > Truing Sleeves



Truing Sleeve

All our mandrels are delivered with the relatives Truing Sleeves in cast Iron, to obtain a perfect alignment between the stones and guides-shoes. More the alignment is accurate, easier will be the working to obtain the desired result. The hole of the Truing Sleeve is that of Diameter of Reference of the capacity:

- Ø 42 mm (1.65") for 60cc
- Ø 50 mm (1.96") for 100cc
- Ø 54 mm ( 2.12) for 125cc.

All rights reserved. Design and specification are subject to change without notice



**EFFECIEMME s.n.c. di Cereda M. & C.**  
Via dell'Artigianato, 22  
20881 BERNAREGGIO (MB) Italia  
tel.: +39 039 6902705 - fax: +39 039 6902932  
e-mail: [effeciemme@effeciemme.com](mailto:effeciemme@effeciemme.com)  
web site: [www.effeciemme.com](http://www.effeciemme.com)

DEALER

